

MOBIHEL®

... for the cars we love


2K ELASTIC ADDITIVE

Used to increase the elasticity of the material for partly plastic parts.
20- 30% will be added to component A, Filler or Clearcoat.
2K hardener will be added in the ratio prescribed for individual product.
When using of MOBIHEL 2K elastic additive VOC the drying of coating
will be slightly extended.



PACKING DATA**Packing:**
6 x 0.5 l**Index:**
47056501**HYGIENE & PERSONAL PROTECTION****TECHNICAL CHARACTERISTICS****Colour:** Colorless
Product type: Unsaturated polyester resin
Density: 1,040 g/ml**SUBSTRATE PREPARATION**

If plastic parts were damaged, apply after cleaning MOBIHEL Primer for plastic low VOC, then MOBIHEL PE putty for plastic and then MOBIHEL 2K HS 4:1 compactprimer low VOC, in which you add 20 – 30 % MOBIHEL 2K elastic additive VOC. As the final two-layer coating you use MOBIHEL Base and MOBIHEL 2K Clearcoat, in which you add 20 – 30 % MOBIHEL 2K elastic additive VOC.

PRODUCT PREPARATION/MIXING**MOBIHEL FILLERS or MOBIHEL CLEARCOATS****MOBIHEL 2K hardener 1100 or 1300 or 1500 or 4100 or 4300 or 4500**
MOBIHEL 2K hardener 700 or 750W

In ratio as it is prescribed for individual products

NOTE:

At use of MOBIHEL 2K elastic additive the drying of coating will be slightly extended.

SHELF LIFE**Shelf life:**

4 years

SAFETY ADVICE

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid release to the environment. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If skin irritation occurs: Get medical advice/attention. In case of fire: use powder, foam or CO2 for extinction.

ONLY FOR PROFESSIONAL USE